



SOFTENER SAFETY DATA SHEET

Issue Date: 09-May-2018

Revision Date: 01-Feb-2019

Version: 2

SECTION 1: Identification

Product identifier: Softener

Other means of identification: Softener – Laundry Softener

Product code: 78025, 78026, 78027.

UN/ID No.: -

Recommended use: Laundry care.

Recommended restrictions: Not for personal care.

Supplier/Distributor information:

Company name: Triple S
Address: 2 Executive Park Drive
Billerica, MA 01862
URL: www.triple-s.com
Email: info@triple-s.com
Telephone: (978)-667-7900
Emergency phone number: (888)-779-1339 (24 hr)

SECTION 2: Hazard(s) identification

Classification of the Substance or Mixture:

Physical hazards:

Health hazards:

| | |
|----------------------------|-------------|
| Acute toxicity, oral: | Category 4 |
| Skin corrosion/irritation: | Category 2 |
| Eye damage/irritation: | Category 2B |

Label elements:



Signal word: Warning

Hazard statements:

| | |
|------|-------------------------|
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H320 | Causes eye irritation. |

Section 2: Hazards Identification (continued)

Precautionary statements

Prevention

| | |
|------|--|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P103 | Read label before use. |
| P262 | Do not get in eyes, skin, or on clothing. |
| P264 | Wash hands thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this products. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |

Response:

| | |
|----------------|--|
| P301+310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. |
| P302+352 | IF ON SKIN: Wash with plenty of water. |
| P304+P312 | IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P332+P313 | If skin irritation occurs: Get medical advice/attention. |
| P337+P313 | If eye irritation persists: Get medical advice/attention. |
| P370+P378 | In case of fire: Use the Manufacturer/supplier or the competent authority to specify appropriate media to extinguish. |

Storage:

| | |
|------|-----------------------------------|
| P403 | Store in a well-ventilated place. |
|------|-----------------------------------|

Disposal:

| | |
|------|--|
| P501 | Dispose of contents/container in accordance with local/ regional/ national/ international Regulations. |
|------|--|

Hazard(s) not otherwise

Classified (HNOC) Not Classified

SECTION 3: Composition/information on ingredients

Substance/Mixtures

| Chemical name | CAS Number | Concentration (%) |
|--|------------|-------------------|
| Water | 7732-18-5 | 80-95 |
| Methyl bis-2-hydroxyethyl Ammonium methyl sulfate | 68410-69-5 | 5-15 |
| Polyethylene glycol monoisodecyl ether | 61827-42-7 | 0-5 |
| Propan-2-ol | 67-63-0 | 0-1 |

SECTION 4: First-Aid Measures

Description of first aid measures

General advice: Remove victims from the danger zone without endangering your own safety. Remove contaminated clothing (including underwear and shoes) immediately.

Inhalation: Bring accident victims out into the fresh air. If patient has difficulty breathing, administer oxygen, keep the patient calm and warm. In case of unconsciousness place patient stably in side position for transportation. Call a physician immediately.

Skin contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before re-use. After contact with small amounts get medical attention if any discomfort or irritation continues. For large amounts, obtain medical attention.

Eye contact: Immediately flush eyes with gentle but large stream of water or eye wash solution for at least 15 minutes, lifting lower and upper eyelids occasionally. If possible remove any contact lenses and continue to wash. Call a physician, immediately.

Ingestion: If swallowed, rinse mouth with water (only if the person is conscious). Never give anything by mouth to an unconscious person. DO NOT induce vomiting, medical advice is required. Call a physician, immediately.

Most important symptoms/effects, acute and delayed:

Notes to physician: The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation: Irritation of nose, throat and airway.

Ingestion: May cause nausea and/or vomiting. Irritation of the mouth, throat, esophagus and gastrointestinal tract.

Skin contact/Skin irritation: Redness or rash may occur.

Eye contact: Causes irritation of the eyes. Possible corneal damage. May cause conjunctivitis Lachrymation. May cause burns.

Indication of immediate medical attention and special treatment needed if necessary:

Cases of eye contact and ingestion should be treated immediately. Have facilities in place to wash skin and eyes in case of exposure.

SECTION 5: Fire-fighting measures

Suitable extinguishing media: This product is flammable by OSHA criteria. In case of fire use carbon dioxide (CO₂), foam, extinguishing powder. In cases of larger fires, water spray should be used. Use any means suitable for extinguishing surrounding fire. Water spray may be used to keep fire-exposed containers cool. If water is used, use in abundance to control heat.

Unsuitable extinguishing media: Do not use water jet as this can spread the fire. Do not use carbon dioxide in enclosed spaces with insufficient ventilation.

SECTION 5: Fire-fighting measures (continued)

Specific hazards arising from the chemical: Fire may produce irritating, corrosive and/or toxic gases. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Move containers from fire area if you can do so without risk. Product containers can melt in the heat of a fire. Packaging materials will be combustible and provide fuel for the fire. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray. For massive fire in cargo, use unmanned hose holder or monitor nozzles. If not, withdraw and let fire burn out.

Special protective equipment and precautions for fire-fighters: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. During fire-fighting respirator with independent air-supply and airtight garment is required. Fight fire in early stages if safe to do so. Containers at risk of fire should be cooled with water and, if possible removed from the danger area. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate area of leak or spill. Ensure adequate ventilation/exhaust extraction. Put on protective equipment (see Section 8). Have emergency procedures in place for treating spillages, evacuating the area and informing the emergency services if necessary. Restrict access to the area until the spillage is treated, if large amounts of vapors are produced that will be hazardous to others, evacuate the area. When any other effects of spillages will affect the safety of others the area should be evacuated. Avoid ingestion, inhalation of vapors and contact with skin and eyes. Non-emergency personnel should be kept away from the area of spillage.

Environment precautions: Clean up any spillages immediately; prevent material from spreading and entering drains or sewage systems. Large spillages or uncontrolled discharge to water systems must be alerted to the Environmental Agency or other regulatory body. If spillages to land cannot be treated safely or if contamination will occur the Environment Agency must be alerted immediately. If the product has entered a foul drain or sewage system in significant amounts to cause a hazard then the local water treatment company must be informed.

Methods and materials for containment and cleaning up: Contain and recover liquid when possible. Small spillages should be absorbed with an inert, non-combustible absorbent. Large Spillages: Dam and absorb spillages with sand, earth or other inert material. Small quantities can be wiped up with absorbent material (e.g. cloth, fleece.) Fit drain covers where they are available if the spillage is likely to enter the drainage system. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Containers with collected spillage must be properly labeled with correct contents and hazard symbol. Flush area clean with lots of water. Be aware of potential for surfaces to become slippery. Ventilate area and allow drying before allowing access. Wash thoroughly after dealing with a spillage.

Reference to other sections: Refer to sections 8 and 13 for additional information.

SECTION 7: Handling and Storage

Precautions for safe handling: Keep in a tightly closed container and protect from physical damage. Store in a cool, dry, ventilated area away from sources of heat, moisture, incompatibilities, and away from direct sunlight. Do not mix with incompatible substances or mixtures. Avoid spilling the product. Do not wash out container and use it for other purposes. Avoid ingestion of the product, inhalation of any vapors/mists when produced and contact with skin and eyes. Do not eat, drink or smoke when handling. Wash at the end of each work shift, before eating, drinking, smoking and using the toilet. Remove contaminated clothing/footwear/equipment before entering eating areas or places that would expose others to the product. Do not use in areas close to drainage systems unless measures are in place to prevent access of product. Ensure emergency procedures are in place to treat spillages and cope with other situations such as evacuation. Provide eye washing and skin washing facilities, when handling large amounts a safety shower is recommended. Observe all warnings and precautions listed for the product.

Conditions for safe storage, including any incompatibilities: Store in closed original container at temperatures between 40°F and 80°F. If the product is transferred to another container, this should be made of a compatible material to the original container. Store away from heat, direct sunlight and moisture. Store in a stable situation to avoid spillages. It is advisable to store in a bunded area or use other protective measures such as a sump pallet or storage tray.

SECTION 8: Exposure control/personal protection

Control Parameters

Occupational exposure limits

US.OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Chemical Name | CAS-No. | Type | Values | |
|-----------------------|------------|------|---------|-----------------------|
| Propan-2-ol | 67-63-0 | PEL | 400 ppm | 980 mg/m ³ |
| Polythethylene glycol | 25322-68-3 | TWA | | 10 mg/m ³ |

U.S. ACGIH Threshold Limit Values

| Chemical Name | CAS-No. | Type | Values | |
|---------------|---------|------|---------|---------|
| Propan-2-ol | 67-63-0 | BEI | | 40 mg/L |
| | | STEL | 400 ppm | |
| | | TWA | 200 ppm | |

Appropriate engineering controls:

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the defined exposure limit requirements or guidelines. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition for details.

Individual protection measures, such as personal protective equipment (PPE)

Eye Protection: Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

SECTION 8: Exposure control/personal protection (continued)

Hand protection: Wear protective gloves. Butyl rubber, rubber (natural, latex), nitrile, polyvinyl chloride (PVC). Be aware that latex gloves can produce an allergic reaction in sensitive individuals. Gloves should have a breakthrough time sufficient for the amount of handling but allow dexterity for safe movement and handling. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Gloves showing signs of degradation should be changed to avoid skin contamination. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. When removing used gloves apply proper technique by avoiding skin contact with the outer surface. When packages of the product are being handled during storage or transport it is advisable to wear protective gloves to prevent damage to the skin.

Personal Respirators (NIOSH Approved): If the exposure limit is exceeded, a full face piece respirator with high efficiency dust/mist filter may be worn up to 50 times the exposure limit. Wear suitable respiratory protection when vapors or mists are produced if the Workplace Exposure Limit is exceeded and there is insufficient ventilation or extraction. For emergencies or instances where the exposure levels are not known, use a full face piece positive-pressure, air-supplied respirator. Respirator must be fitted with a cartridge suitable for the chemical of concern. Consult with the supplier as to the compatibility of the equipment with the chemical of concern. CAUTION: Air purifying respirators do not protect the user in oxygen deficient atmospheres, use air supplied system.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations: Wash hands, change out of clothes as soon as possible. Wash clothes. Shower or bathe as soon as possible.

Other protective measures: Have an eye bath and safety shower close by.

SECTION 9: Physical and chemical properties

| | |
|--|-------------------|
| Appearance: | Liquid |
| Color: | White |
| Odor: | Aromatic |
| Odor Threshold: | No data available |
| pH: | 5.0 ± 0.5 |
| Melting point/range: | No data available |
| Boiling point/range: | No data available |
| Flash point: | No data available |
| Evaporation rate: | No data available |
| Flammability (solid, gas): | No data available |
| Upper/lower flammability of explosive limits: | No data available |
| Vapour pressure (mm Hg): | No data available |
| Vapour density (Air=1): | No data available |
| Relative density: | No data available |
| Solubility(ies): | Excellent |
| Partition coefficient (n-octanol/water): | No data available |
| Auto-ignition temperature: | No data available |
| Decomposition temperature: | No data available |
| Viscosity, dynamic: | No data available |

Other Information: This product contains no phosphates.

SECTION 10: Stability and Reactivity

Reactivity and/or Chemical stability: If stored and handled in accordance with standard industrial practices no hazardous reactions are known. Product is very stable under normal conditions.

Possibility of hazardous reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Avoid heat, direct sunlight, and moisture. Avoid storage with incompatible materials. Avoid storage in freezing conditions. Avoid storage near to unprotected drainage systems. Avoid storage in an unstable manner or in a situation that would result in exposure to the product. It is advisable to store the product within some form of containment to prevent spillages reaching drainage systems. Do not allow the storage container to be left exposed to the atmosphere.

Incompatible Materials:

-Strong oxidizers -Strong acids -Strong bases -Chlorine

Hazardous Decomposition Products: Mild decomposition can result giving off hydrogen.

SECTION 11: Toxicological information

Acute toxicity: Toxicological testing has not been conducted with this material. The toxicology information listed below us based on the components of this material.

| |
|---|
| Methyl bis-2-hydroxyethyl ammonium methyl sulfate – Acute Toxicity Estimate (ATE) |
| ATE _{Mix} (oral) > 2,000 mg/kg |

Skin Corrosion/ irritation: Category 2: Cause skin irritation.

Serious eye damage/irritation: Category 2B: Causes eye irritation.

Respiratory or skin sensitization: Classification not possible.

Germ cell mutagenicity: Classification not possible.

Carcinogenicity: Classification not possible.

Reproductive toxicity: Classification not possible.

Specific Target Organ Toxicity - Single Exposure: Classification not possible.

Specific Target Organ Toxicity - Repeated Exposure: Classification not possible.

Aspiration hazard: Classification not possible.

SECTION 12: Ecological information

Do not allow to escape into waterways, wastewater or soil.

Toxicity: Ecotoxicological studies of the product are not available. Please find below the data available to us from raw materials:

Aquatic ecotoxicity

| Propan-2-ol |
|--|
| LC ₅₀ Bluegill (<i>Lepomis macrochirus</i>) > 1,400 mg/L Fresh Water: 96 hrs |

Persistence and Degradability: No data is available on the degradability of this product.

Bioaccumulative Potential: No data available for this product.

Mobility in Soil: No data available for this product.

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

General information

Do not allow unauthorized disposal to the environment. If operators are exposed to vapors during the disposal process then suitable respiratory protection should be worn. All other personal protective equipment as described in section 8 should be worn.

Disposal methods:

Avoid unauthorized disposal. Do not dump into any sewers, on the ground, or into any body of water. All disposal practices must be in compliance with federal, state/provincial and local laws and regulations. For a small spill, immediately hose down with cool water and dispose to drain. For a large spill, dike, collect and contact local authorities about disposal.

SECTION 14: Transport Information

| | |
|--------------------------------------|--------------------|
| UN Number: | Not Available. |
| UN Proper Shipping Name: | Not Applicable. |
| Transport hazard class(es): | |
| DOT Hazard Class: | Not Available. |
| DOT Subsidiary Hazard Class: | Not Available. |
| Packing group, if available: | Not Available. |
| Environmental Hazards: | No |
| Special precautions for user: | Not DOT regulated. |

Transport in bulk according to Annex II of MARPOL 73/78³ and the IBC Code ³: Not applicable.

SECTION 15: Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Unless otherwise noted, no components are SARA TITLE 3 SECTION 313 40 CFR listed materials.
The ingredients of this product are listed on the TSCA inventory.
This product is not made with VOC'S that could cause damage to the ozone layer.

State Regulations

US- New Jersey RTK- Substances: Listed substance

Propan-2-ol (CAS 67-63-0)
Substance no. 1076

SECTION 16: Other Information including date of preparation or last revision

Chemical State: Liquid

Chemical Type: Mixture

| | |
|---|---------------------|
| 2 | Health |
| 0 | Flammability |
| 0 | Physical Hazard |
| B | Personal Protection |

To the best of our knowledge, the information contained herein is accurate. **However, neither U.N.X. Incorporated nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.** Final determination of suitability of any material is the sole responsibility of the user. All materials may represent unknown hazards and should be used within caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.